

AKROSTOP eristyspohjamaali (Sealing Paint)

Date 27.6.2012

Previous date: 17.10.2007

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier**
- 1.1.1 Commercial Product Name**
AKROSTOP eristyspohjamaali (Sealing Paint)
- 1.1.2 Product code**
006 5663
- 1.2 Relevant identified uses of the substance or mixture and uses advised against**
- 1.2.1 Recommended use**
Painting work.
Description: Water-borne acrylate paint.
- 1.3 Details of the supplier of the safety data sheet**
- 1.3.1 Supplier**
Tikkurila Oyj
- P.O.Box** P.O.Box 53
Postcode and post office FI-01301 VANTAA
FINLAND
- Telephone** +358 9 857 71
Telefax +358 9 8577 6936
- 1.3.4 Responsible for the Safety Data Sheet:**
Tikkurila Oyj, Product Safety, e-mail: productsafety@tikkurila.com
- 1.4 Emergency telephone number**
- 1.4.1 Telephone number, name and address**
Tikkurila Oyj, Environment and Safety: +358 9 857 71 (Mon-Fri 8-16 Finnish time)

2. HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture**
The product is not classified as dangerous in accordance with EU Directive 1999/45/EC.
- 2.2 Label elements**
The product does not have a warning label.
- 2.3 Other hazards**
Other hazards are not known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures		Hazardous components		Chemical name of the substance	Concentration	Classification
CAS number	EINECS					
-	-	-	-	-	-	-

4. FIRST AID MEASURES

- 4.1 Description of first aid measures**
In all cases of doubt, or when symptoms persist, seek medical attention.
- 4.1.2 Inhalation**
Remove to fresh air.
- 4.1.3 Skin contact**
Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use solvents or thinners.
- 4.1.4 Eye contact**

AKROSTOP eristospohjamaali (Sealing Paint)

Date 27.6.2012

Previous date: 17.10.2007

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 15 minutes and seek medical advice if necessary.

4.1.5 Ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious). Obtain medical attention, when necessary.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of immediate medical attention and special treatment needed

None.

5. FIREFIGHTING MEASURES**5.1 Extinguishing media****5.1.1 Suitable extinguishing media**

The product is water based and is not flammable. If necessary, use alcohol resistant foam, CO₂, powders or water spray/mist.

5.1.2 Extinguishing media which must not be used for safety reasons

None known.

5.2 Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures**

Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Do not allow to enter drains or water courses.

6.3 Methods and materials for containment and cleaning up

Contain and collect spillage with absorbent materials, e.g. sand or vermiculite and place in a container for disposal according to local regulations. Clean preferably with water or detergent; avoid the use of solvents.

6.4 Reference to other sections

See also Section 13 for waste disposal instructions.

7. HANDLING AND STORAGE**7.1 Precautions for safe handling**

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Avoid inhalation of dust from sanding. Smoking, eating and drinking should be prohibited in application area.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated place. Keep away from oxidising agents, from strongly alkaline and strongly acid materials. No smoking. Keep container tightly closed. Do not allow to freeze.

7.3 Specific end use(s)

None.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters**

AKROSTOP eristospohjamaali (Sealing Paint)

Date 27.6.2012

Previous date: 17.10.2007

The product does not contain reportable concentrations of substances with the exposure limit values (Occupational Exposure Limit Values according to EU Directives and Threshold Limit Values according to ACGIH 2009).

8.2 Exposure controls**8.2.1 Appropriate engineering controls**

Provide adequate ventilation.

8.2.2 Individual protection measures**8.2.2.1 Respiratory protection**

If ventilation during spray-application is insufficient, use appropriate certified respirators with gas, vapour and dust filter AP.

8.2.2.2 Hand protection

Always wear protective gloves.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Gloves should be replaced regularly and if there is any sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Recommended protective glove type is e.g.:

nitrile rubber (breakthrough time > 480 min.)

PVA gloves are not recommended.

8.2.2.3 Eye/face protection

Use safety eyewear, specially during spray-application.

8.2.2.4 Skin protection

Wear suitable protective clothing during spray-application.

9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Important Health Safety and Environmental Information****9.1.1 Appearance**

Coloured, viscous liquid

9.1.6 Initial boiling point and boiling range

-

9.1.7 Flash point

-

9.1.10 Explosive properties**9.1.10.1 Lower explosion limit**

-

9.1.10.2 Upper explosion limit

-

9.1.11 Vapour pressure

-

9.1.13 Relative density

1,4

9.1.14 Solubility(ies)**9.1.14.1 Water solubility**

Soluble

9.2 Other information

None.

10. STABILITY AND REACTIVITY**10.1 Reactivity**

See section 10.5.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

See section 10.5.

10.4 Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

AKROSTOP eristospohjamaali (Sealing Paint)

Date 27.6.2012

Previous date: 17.10.2007

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

Hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc. may produce when exposed to high temperatures.

11. TOXICOLOGICAL INFORMATION**11.1 Information on toxicological effects**

There are no toxicological test data available on the product itself.

11.1.3 Sensitisation

The product is not classified as sensitizing by skin contact, but it contains small amounts of preservatives or other biocides which may produce an allergic reaction: 1,2-benzisothiazol-3(2H)-one and 2,2-dibromo-3-nitrilopropionamide and 2,2'-dithiobis(N-methylbenzamide)

11.1.8 Other information on acute toxicity

Inhalation: Long term exposure to spray mist may cause irritation of respiratory system.

Skin contact: Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis. The liquid splashed in the eyes may cause irritation.

Ingestion: Ingestion may cause nausea.

12. ECOLOGICAL INFORMATION**12.1 Toxicity****12.1.1 Aquatic toxicity**

No relevant data.

12.2 Persistence and degradability**12.2.1 Biodegradation**

No relevant data.

12.3 Bioaccumulative potential

No relevant data.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

There is no ecotoxicological test data available on the product itself. The product should not be allowed to enter drains or water courses.

The product is not classified as environmentally hazardous.

13. DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods****Product residues:**

Gather residues into waste containers. Destroy according to the rules given by local authorities. EWC-code for liquid waste is e.g 08 01 11 or 08 01 12 (waste paint and varnish).

Packaging waste:

Empty cans should be recycled or disposed of in accordance with local regulations.

14. TRANSPORT INFORMATION

14.1 UN number None

14.2 UN proper shipping name None

AKROSTOP eristyspohjamaali (Sealing Paint)

Date 27.6.2012

Previous date: 17.10.2007

14.3	Transport hazard class(es)	Not classified
14.4	Packing group	None
14.5	Environmental hazards	
		The product is not classified as environmentally hazardous according to international transport regulations.
14.6	Special precautions for users	
		None known.
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	
		None known.

15. REGULATORY INFORMATION

15.1	Safety, health and environmental regulations/legislation specific for the substance or mixture	None known.
15.2	Chemical safety assessment	Has not been performed.

16. OTHER INFORMATION

16.8	Additional information	
		This Safety Data Sheet is prepared in accordance with Annex II (EU) No 453/2010 to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. Additional information available from: Tikkurila Oyj, Product Safety, P.O. Box 53, FIN-01301 VANTAA, FINLAND, Telephone +358 9 857 71, Fax +358 9 8577 6936, E-mail: productsafety@tikkurila.com
	Signature	g/rpa